



WALLUX

WL01X SERIES

OUTDOOR

WALLUX

WL01X SERIES



SPECIFICATIONS :

Housing	: Die-cast aluminum
Lamp Type	: TC-D CFL
Lamp holder	: G24
Voltage rating/ freq.	: 220-240V / 50-60 Hz
Control gear type	: HF electronic control gear
Power factor	: >0.95
Degree of protection	: IP 65
Optical configuration	: Anodized aluminium reflector
Finishing	: UV stabilized polyester powder coating, resistant to corrosive environment.
Light controller	: Opal PC diffuser.

DESCRIPTIONS : WALLUX WL01X Series is a general purpose bulkhead luminaire for outdoor applications. Using of high quality die cast aluminium housing and Opal PC diffuser make this product suitable for the most severe conditions with protection degree IP 65.



APPLICATIONS : Roof lightig, building surrounding, electrical and mechanical rooms and other similar outdoor applications.





OUTDOOR

WALLUX



WL01X SERIES





CODE	D	H
WALLUX [WL011]-1x18/26 W TC-D	265	120
WALLUX [WL012]-2x18/26 W TC-D	365	143



CODE	D	H
WALLUX [WL013]-1x18/26W TC-D	265	120
WALLUX [WL014]-2x18/26 W TC-D	365	143



CODE	D	H
WALLUX [WL015]-1x18/26 W TC-D	265	120
WALLUX [WL016]-1x18/26 W TC-D	365	143



CODE	D	H
WALLUX [WL017]-1x18/26 W TC-D	265	120
WALLUX [WL018]-2x18/26 W TC-D	365	143

OPTIONS:
Emergency Kit [EM1.5] [EM3]

Head office

Malaz - Salahidin Road
P.O Box 1246 Riyadh 11431

Tel : +966 11 477 77 00
Fax: +966 11 478 94 69

Western Region Office

Tahliya Street
P.O Box 20798 Jeddah 21465

Tel : +966 12 6650888
Fax: +966 12 6633413

Eastern Region Office

King Abdulaziz Street
P.O Box 8492 Dammam 31482

Tel : +966 13 8336509
Fax: +966 13 8329065

ContactUs@noortek.com



www.noortek.com